

Vacuum Metal Sheet Lifter serie F10EB 2000

Technical specification

Application	Metal sheet, stainless steel, aluminum, plastic panels					
Lifting capacity	2000 kg					
Suction pads	No. 10 suction pads in vulcanized rubber, diameter 310 mm Suction pads with spring supports Exclusion of suction pads by cross arm					
Frame	Steel frame structure fixed in horizontal position The suction pads are distributed on three cross arms Adjustable position of suction pads and of cross arms					
Operating system	Electric 400V 3 phase 50Hz or 220V 1 phase 50Hz > to specify at order					
Vacuum system Safety systems	Vacuum circuit with vacuum reservoir, non-return valve, vacuum filter Vacuum gauge with colored scale Audio visual low vacuum waring powered independently and with back up battery					
Weight of lifter	Depends on the configuration					
Command	command Suction and release by slide valve command with safety system					







SILCOMNORTH UAB

www.silcomnorth.com hello@silcomnorth.com Phone +370 67216691 Antakalnio g. 17, Vilnius 10312, Lithuania

• Electric operating system

- 10 suction pad d.310 mm
- fixed frame for horizontal lifting
- lifting capacity 2000 kg

• Safety devices

CE

Available models

Pads		Capacity	L	Arms		X (mm)		Y (mm)		Product Code
nr.	Ø	kg	mm	nr.	mm	min*	max	min	max	
10	310	2000	3000	5	1270	2 450*	3150	720	1500	F10EB2000/3-3000/1270
			4000	5	1270	2450*	4150	720	1500	F10EB2000/3-4000/1270

* min quote working with only 6 pads and excluding two external arms : 1170 mm

