

The sheet metal vacuum lifter F4B is battery powered by high capacity rechargeable batteries (battery charger is included). F4B 600 has a maximum capacity of 600 kg and **4 suction pads** distributed on 2 cross-arms. The pads, equipped with springs, are made of **special oil-resistant vulcanized rubber**, specific for sheet metal.

The lifter can be produced with different crossbeam lengths, from L1500 mm to L4000 mm (different lengths on request). Adjusting the position of the pads and arms allows you to **adapt the vacuum lifter to the different sizes and shapes** of the sheets metal. The F4B 600 model has a **steel reinforced supporting structure** and a horizontal fixed frame.




Technical specification

Application	Metal sheet, stainless steel, aluminium, plastic panels	
Lifting capacity	600 kg	_
Suction pads	Nr. 4 vacuum pads d. 310 mm	
Frame	Steel frame structure fixed in horizontal position	
	The suction pads are distributed on 2 cross arms	
	Adjustable position of suction pads and of cross arms	
Operating system	Battery operating system DC vacuum pump powered from on-board batteries	
	High capacity re-chargeable batteries, battery status indicator	
	Economizer for reduction of the energy consumption	
Vacuum system	Vacuum circuit with vacuum reservoir, non-return valve, vacuum filter	mada in
Safety systems	Vacuum gauge with colored scale	<u>made in</u>
	Audio visual low vacuum waring powered independently and with back up battery	ΙΤΛΙ ۷
Weight of lifter	Depends on the configuration	IIALI
Command	Suction and release by slide valve command with safety system	_
Optional	Radio remote control (for suction and release at a distance)	_
-	Support for forklift	



Vacuum lifter

Technical drawing



Model F4B



Pads		Capacity	Crossbeam	Arms		X (mm)		Y (mm)		Product code
nr.	Ø	kg	mm	nr.	mm	min	max	min	max	
4	310	600	1500	2	830	1145	1655	635	1000	F4B600/3-1500/750
			2000	2	830	1145	2155	635	1000	F4B600/3 -2000/750
					1330	1145	2155	635	1500	F4B600/3-2000/1270
			3000	2	830	1145	3155	635	1000	F4B600/3-3000/750
					1330	1145	3155	635	1500	F4B600/3-3000/1270