

The Vacuum Lifter for sheet metal F8EB is a model with **electric operating system**, it can be produced 400V three-phase or 220V single-phase. The model F8EB 1500 has a maximum capacity of 1500 kg. The **crossbeam can have different lengths**, on standard models it is L3000 mm or L4000 mm and the 8 suction pads are distributed on 4 arms. The pads, equipped with springs, are specific for sheet metal made in **special oil-resistant vulcanized rubber**.

The adjustment of the position of the pads and arms, together with the possibility of **using only the central plates**, allows to adapt the lifter to the different formats of the metal sheets to be lifted. The F8 1500 model has a steel reinforced structure and a horizontal fixed frame.



Technical specification


Application	Metal sheet, stainless steel, aluminum, plastic panels	
Lifting capacity	1500 Kg	
Suction pads	Nr. 8 vacuum pads d. 310 mm	
Frame	Steel frame structure fixed in horizontal position	
	Lowered below the hook height	
	The suction pads are distributed on cross arms	
	Adjustable position of suction pads and of cross arms	
Operating system	Electric 400V 3 phase 50Hz or 220V 1 phase 50Hz	mada in
Vacuum system	Vacuum circuit with vacuum reservoir, non-return valve, vacuum filter	made in
Safety systems	Vacuum gauge with colored scale	ΙΤΔΙΥ
	Audio visual low vacuum waring powered independently and with back up battery	
Weight of lifter	Depends on the configuration	
Command	Suction and release by slide valve command with safety system	


SHEET METAL division

Vacuum lifter



Technical drawing





Series F8EB 1500



Pads		Capacity	L	Arms		X (mm)			Y (mm)		Product code
nr.	Ø	kg	mm	nr.	mm	X1	min	max	min	max	
8	310	1500	3000	4	830	1145	2115	3065	635	1000	F8EB1500/3-3000/750
					1330	1145	2115	3065	635	1500	F8EB1500/3-3000/1270
			4000	4	1330	1145	2115	4065	635	1500	F8EB1500/3-4000/1270

Righetti Vacuum Lifters Specialists