

The model P5A625K-X is a **transformable vacuum lifter** with 5 pads and lifting capacity **625 kg**. Thanks to two extension arms (L 830mm), this lifter can change configuration from inline-pads, **suitable for kitchen tops**, to cross-pads, **suitable for big slabs**. The standard central beam is 2400mm long. All the 5 vacuum pads feature **support for quick rotation**.

It is powered by compressed air, featuring a **pneumatic tilting system** which allows an assisted vertical — horizontal movement of the load and vice versa, controlled by a joystick on lifter's handle. It is equipped with an **audio-visual alarm** control unit that warns the operator of possible dangerous situations. The vacuum gauge with coloured scale allows constant control of the vacuum level reached. It is equipped with a **filtering system for dust and condensation**.

## **Technical specification**

Application	Not porous materials – Marble and granite slabs / kitchen tops	
Lifting capacity	Kg 625	
Suction pads	Nr. 5 rotative suction pads mm 480x230	
Load movement	Powered tilt 0-90°. Activation of tilting by joystick command	
Operating system	Compressed air	
Vacuum system	Vacuum circuit, complete of vacuum reserve and non return valve	
Control	Manual valve on the lifter's frame	
	Release of the load by dual action security command	
Standard features	On-off double sliding valve with safety	
	Audible and visual low vacuum warning devices	
	Vacuum gauge with colored scale, vacuum filter, non return valves	
Optional	White gaskets	
	Parking stand with wheels	
	Holder for hoist command	



## Kitchen top vacuum lifter

## **Technical drawing**

