Vacuum glass lifter



The model VA2 RCMBP d4 is a vacuum glass lifter specific for indoor use, with two suction pads d. 390 mm, compressed air powered with lifting capacity up to 300Kg. The pads are replaceable along the beam in different positions. The standard central beam is 1500mm long, on request different lengths.

Thanks to its pneumatic cylinder, this lifter features **powered 0 – 90° tilt controlled by joystick**, placed on the lifter's handle. It also has manual 360° rotation with automatic locking each 90°. It is guipped with an audio-visual alarm unit that warns the operator of possible dangerous situations. The vacuum gauge with coloured scale allows constant control of the vacuum level reached. It features a **filtering system** for dust and condensation.

Technical specification

Application	Glass panels	
Lifting capacity	Max 300 kg	Indoor use
Suction pads	No. 2 round suction pads diameter 390 mm	
	Lipped pads with safety ring	Safety devices
Pad spread	Various pads configurations	
Load movement	360° manual rotation, with possibility of automatic locking each 90°	Manual tilt 0-90°
	Pneumatic 90° tilt, controlled by joystick	
Operating system	Compressed air	350'
Vacuum system	Single vacuum circuit with vacuum reserve and non return valve	Manual rotation 360°
Weight of lifter	Kg 59	
Control	Manual on off valve on the lifter's frame	
	Release of the load by dual action security command	
Standard features	Audible and visual low vacuum warning devices	
	Vacuum gauge, Vacuum filter,	
	Adjustable pads position	- <u>made in</u>

Righetti Vacuum Lifters Specialists