# Taighetti smart vacuum lifters

## Vacuum glass lifter

Model VA4 BP







The model VA4 BP is a **vacuum glass lifter specific for indoor use**, with four suction pads d. 310 mm, compressed air powered with lifting capacity 400Kg. The pads are replaceable along the arms; and the arms are replaceable along the central beam, which is long 1500 mm.

Thank to its pneumatic cylinder the lifter features **powered 0 – 90° tilt**, controlled by a joystick on the lifter's handle. Equipped with an audio-visual alarm control unit that warns the operator of possible dangerous situations. The vacuum gauge with coloured scale allows constant control of the vacuum level reached. Present a **filtering system** for dust and condensation.

This model is also available with suction pads d. 390 mm and lifting capacity 600kg.



Pneumatic tilt 0-90°



Capacity max 400kg



**V** 

Audio-visual alarm



Safety devices



4 vacuum pads d.310 mm




Indoor use



## Vacuum glass lifter

### **Technicaldrawings**



### **Technical specification**

| Application       | Glass panels   |
|-------------------|--|
| Lifting capacity  | Max 400 kg   |
| Suction pads      | No. 4 round suction pads diameter 310 mm                       |
|                   | Lipped pads with safety ring                                   |
| Pad spread        | Various pads configurations:                                   |
|                   | Min about 9860x720 mm  |
|                   | Max about 1640x1000 mm   |
| Load movement     | 90° degree pneumatic tilt                                      |
| Operating system  | Compressed air   |
| Vacuum system     | Signle vacuum circuit with vacuum reserve and non return valve |
| Weight of lifter  | Kg 80  |
| Control           | Manual on off valve on the lifter's frame                      |
|                   | Release of the load by dual action security command            |
| Standard features | Audible and visual low vacuum warning devices                  |
|                   | Vacuum gauge, Vacuum filter, Adjustable arms position          |
|                   | Adjustable pads position                                       |