

Vacuum glass lifter

VB4 RCEBE d4 PRO









The VB4 RCEBE d4 PRO is a version of the standard VB4 vacuum glass lifter completed with four **extension arms** for bigger pad spread. Thanks to its extension arms, this lifter can reach **four different configurations**. The four suction cups can be put **in in-line position** and allow the lifter to handle long and narrow glass.

Vacuum glass lifter VB4 RCEBE d4 is **powered by rechargeable batteries** that, if necessary, may be easily removed and quickly replaced. The VB4 RCEBE d4 vacuum lifter features **electric tilt and electric 360 degree rotation**.

VB4 is specific vacuum glass lifter for construction site use with **dual vacuum circuit** according to EN13155. The same model is also available with vacuum pads d. 310 mm and 400kg capacity (mod. VB4RCEBE PR0).



Electric tilt 0-90°



Electric continuous rotation 360°



Max capacity 600kg



4 vacuum pads d.390 mm



Safety devices



4 possible configurations











Vacuum glass lifter

Technical drawing









Technical specification

	1.
Application	Glass panels
Lifting capacity	Max 600 kg
Suction pads	No. 4 round suction pads diameter 390 mm
	Lipped pads with safety ring
Pad spread	A mm 1019 x 795
	B mm 1246 x 941
	C mm 1630 x 1190
	D mm 1870 x 390
Load movement	Continuous 360 degrees powered rotation
	90 degrees powered tilt
Operating system	DC vacuum pump powered from on-board batteries
	High capacity re-chargeable batteries
	Battery status indicator
	Economizer for reduction of the energy consumption
Vacuum system	2 independent vacuum circuits, each vacuum circuit with vacuum reserve and non return valve
Weight of lifter	Kg 140
Structural depth	mm 614
Control	Radio remote control
	Release of the load by dual action security command
Standard features	Audible and visual low vacuum warning devices
	Vacuum gauge for each vacuum circuit
	Battery charger 240 Volt
	Vacuum filter
	Multi position hook connection