

Righetti

smart vacuum lifters

Model

VEB4+4 RCEBE

Vacuum glass lifter



Kg max
800



Power supply
Electricity



The model VEB4+4 RCEBE is a **modular vacuum glass lifter** with electric movements. On VEB4+4 model, the four external suction pads are on removable extension arms that permit to increase the lifting capacity and the pad spread. The pad arms can be removed quickly and easily. In configuration with 4 pads, the lifting capacity is 400 kg and is possible to lift small glass panels. With addition of four extension pad arms, the lifting capacity increases to 800 kg. The VEB4+4 RCEBE vacuum lifter features **powered tilt 0 – 90° and powered 360° rotation**. The aspiration, release, tilting and rotating commands are by push button cable command.

Vacuum glass lifter VEB4+4 RCEBE is **electric powered**, it can be produced with voltage 220V 1phase or 400V 3phases, 50Hz. This model can be used on production area, but also on construction site since it features **dual vacuum circuit** according to EN13155.

This lifter is also available with suction pads d. 390 mm and capacity 600/1200 kg (mod VEB4+4 RCEBE d4). It's also available with electric rotation and manual tilt (VEB4+4 RCEBM); or with manual rotation and electric tilt (VEB4+4 RCMBE).



Electric tilt 0-90°



Capacity max 800kg



Electric continuous rotation 360°



Safety devices



8 vacuum pads d.310 mm




Dual vacuum circuit

CE

made in
ITALY

Technical drawing



Suction pads		Capacity Kg	Model with		
No.	Ø mm		electric tilt and electric rotation	manual tilt and electric rotation	electric tilt and manual rotation
8	310	800	VEB4+4 RCEBE	VEB4+4 RCEBM	VEB4+4 RCMBE

Technical specification

Application	Glass panels
Lifting capacity	Max 800 kg
Suction pads	No. 4+4 round suction pads diameter 310 mm Lipped pads with safety ring
Pad spread	MAX mm 2145 x 1488 – MIN mm 863 x 666
Load movement	Electric tilt and electric rotation on VEB4+4 RCEBE d4 Manual tilt and electric rotation on VEB4+4 RCEBM d4 Electric tilt and manual rotation on VEB4+4 RCMBE d4
Operating system	Electric operated: 400V 3 phase 50Hz OR 220V single phase 50Hz
Vacuum system	Dual vacuum circuit according to EN13155
Weight of lifter	Kg 152
Structural depth	Mm 614
Control	Suction / release and electric movements controlled by push buttons cable command
Standard features	Audible and visual low vacuum warning devices Vacuum gauge, Vacuum filter Battery charger for alarm system
Optional	Radio remote control