

Righetti

smart vacuum lifters

Vacuum glass lifter

Model

VEB4+4 RCMBM

 Kg max
800

 Power supply
Electricity



The **VEB4+4 RCMBM** model is vacuum glass lifter with eight suction pads d. 310 mm, perfect to lift and handle glass sheets. On VB4+4 model, the **four external suction pads** are on removable extension arms that permit to increase the lifting capacity and the pad spread. The pad arms can be removed quickly and easily.

In configuration with 4 pads, the lifting capacity is 400 kg and it is possible to lift small glass panels. With the addition of four extension pad arms, the lifting capacity increases to 800 kg. Thanks to its extension arms, this lifter can also reach **different configurations**.

VEB4+4 has **electric operating system**. As standard is available 400V 3 phase or 220V single phase operated system 50Hz. On request other voltage. The lifter permits to manually **rotate the glass of 360° and tilt 90°** from horizontal to vertical and vice versa. VEB4+4 can be produced, as optional, with **dual vacuum circuit** according to EN13155 standard. The lifter is also available with suction pads d.390 mm and capacity 1200 kg, mod VEB4+4 RCMBM d4.



Manual tilt 0-90°



Capacity max 800kg



Manual continuous rotation 360°



Safety devices



4+4 vacuum pads d.310 mm




Available with dual vacuum circuit

CE

made in
ITALY

Technical drawings



Technical specification

Application	Glass panels
Lifting capacity	Max 800 kg
Suction pads	No. 8 round suction pads diameter 310 mm Lipped pads with safety ring
Pad spread	MAX mm 2145x1488 MIN mm 863x666
Load movement	Continuous 360 degree rotation, with possibility of automatic locking at each 90° 90 degree tilt, with possibility of automatic locking in upright and flat position
Operating system	Electric operated 400V 3 phase 50Hz OR 220V single phase 50Hz
Vacuum system	Single vacuum circuit As optional dual vacuum circuit
Weight of lifter	Kg 94
Control	Manual on off valve on the lifter's frame Release of the load by dual action security command
Standard features	Audible and visual low vacuum warning devices Vacuum gauge Battery charger for alarm system Vacuum filter Multi position hook connection Lowered suspension for installing of transom window