

Vacuum glass lifter


600 Kg max





The model VEB4 RCEBE d4 is a **modular vacuum glass lifter** with electric movements and lifting capacity 600kg. The VEB4 RCEBE d4 features **powered tilt 0 – 90° and powered continue 360° rotation**. The aspiration, release, tilting and rotating commands are controlled by push button cable command (radio remote control as optional).


Vacuum glass lifter VEB4 RCEBE d4 is **electric powered**, it can be produced with voltage 220V 1phase or 400V 3phases, 50Hz. This model can be used on production area, but also on construction site since it features **dual vacuum circuit** according to EN13155. This lifter is also available with suction pads d. 310 mm and capacity 400 (mod VEB4 RCEBE). It's also available with electric rotation and manual tilt (VEB4 RCEBM d4); or with manual rotation and electric tilt (VEB4 RCMBE d4).






Vacuum glass lifter

Technical drawing





Suction pads		Capacity	Model with		
No.	Ø mm	Kg	electric tilt and electric rotation	manual tilt and electric rotation	electric tilt and manual rotation
4	390	600	VEB4 RCEBE d4	VEB4 RCEBM d4	VEB4 RCMBE d4

Technical specification

Application	Glass panels		
ifting capacity Max 600 kg			
Suction pads	No. 4 round suction pads diameter 390 mm		
	Lipped pads with safety ring		
Pad spread	MAX mm 1246 x 941 – MIN mm 1019 x 795		
Load movement	Electric tilt and electric rotation on VEB4 RCEBE d4		
	Manual tilt and electric rotation on VEB4 RCEBM d4		
	Electric tilt and manual rotation on VEB4 RCMBE d4		
Operating system	Electric operated: 400V 3 phase 50Hz OR 220V single phase 50Hz		
Vacuum system	Dual vacuum circuit according to EN13155		
Weight of lifter	Kg 135		
Structural depth	Mm 614		
Control	Suction / release and electric movements controlled by push buttons cable command		
Standard features	Audible and visual low vacuum warning devices		
	Vacuum gauge, Vacuum filter		
	Battery charger for alarm system		
Optional	Radio remote control		