



## ST1300 TROLLEY

LIFTS UP TO 1,300 KG / 2,866 LBS

A rugged and self-propelled transport trolley for plasterboards and other building materials. The Smart Trolley has an electric lifter which extends up to 90 cm above ground level. Therefore it can be used as a flexible working bench at the construction site for better ergonomics. The trolley also has two side pockets for being lifted by a forklift between the floors of a building

- Self-propelled forward/reverse
- Quality bearings
- Independent wheels
- Puncture-proof tires
- Indicator for low voltage
- IP65 classified dust and moisture proof

### TECHNICAL SPECIFICATIONS

WWL / rated load	1,300 kg / 2,866 lbs
Floor dimensions	1880 x 700 mm / 2,680 x 700 mm 74 x 28 in / 106 x 28 in
Floor height	600 - 900 mm / 23 - 35 in
Total length	2,850 mm / 112 in
Total length (shipped)	2,100 mm / 83 in
Wheel base	1,438 mm / 57 in
Extension - handlebar	220 mm / 9 in
Ground clearance	135 mm / 5 in
Raise / lower floor	10 sec
Driving speeds	Floor raised = 1 kmh / 0,6 mph Floor lowered = 5 kmh / 3,1 mph
Battery	2 x 12V 95Ah
Operation time	Approx. 8 hrs
Turning radius	3,1 m / 10 ft. 2 in
Charger with indicator	Integrated 110V / 230V
Curb weight	450 kg / 1000 lbs



LIFTING CAPACITY

**1300 KG / 2866 LBS**



LIFTING HEIGHT

**90 CM / 35 IN**



ST1300 Trolley comes with steering handle making it easy to operate.



**SMARTLIFT®**

## ST1300 TROLLEY

### TECHNICAL SPECIFICATIONS

SWL / rated load	1,300 kg / 2,866 lbs.
Floor dimensions	1,880 x 700 mm / 2,680 mm x 700 mm
	74 x 28 in. / 106 x 28 in.
Floor height	600 - 900 mm / 23 - 35 in.
Total length	2,850 mm / 112 in.
Total length when shipped	2,100 mm / 83 in.
Wheel base	1,438 mm / 57 in.
Extension - handlebar	220 mm / 9 in.
Ground clearance	135 mm / 5 in.
Raise / lower floor	10 sec.
Driving speeds	Floor raised = 1 km/h / 0.6 mph. Floor lowered = 5 km/h / 3.1 mph.
Battery	2 x 12V 95Ah
Operating time	8 hours
Wheels	Foam-filled off-road tires
Turning radius	3.1 m / 10.2 ft.
Charger with indicator	Integrated 110V / 230V
Curb weight	450 kg / 1,000 lbs.

